

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

Characterist research by the control by the



SC5384.1TR

OFFICE OF NAVAL RESEARCH
Contract NO0014-77-C-0636
Task No. NR 359-667
TECHNICAL REPORT NO. 6

Water Absorption and Conductivity in Poly(Ethylene Oxide)-Lithium Tetrafluoroborate Films

by

M. M. Nicholson and T. P. Weismuller

Prepared for Publication in the

Journal of the Electrochemical Society



Science Center
Rockwell International Corporation
Anaheim, California

October, 1984

Reproduction in whole or in part is permitted for any purpose of the United States Government.

This document has been approved for public release and sale; its distribution is unlimited.

84 11 13 028

SECURITY CLASSIFICATION OF THIS PAGE									
REPORT DOCUMENTATION PAGE									
18 REPORT SECURITY CLASSIFICATION Unclassified		16. RESTRICTIVE MARKINGS							
28. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT This document has been approved for public							
2b. DECLASSIFICATION/DOWNGRADING SCHED	release and sale; its distribution is un-								
4. PERFORMING ORGANIZATION REPORT NUMBER(S) SC5384. TTR		5. MONITORING ORGANIZATION REPORT NUMBER(S)							
64 NAME OF PERFORMING ORGANIZATION Rockwell International Science Center	76. NAME OF MONITORING ORGANIZATION Office of Naval Research								
Sc. ADDRESS (City, State and ZIP Code)	7b. ADDRESS (City, State and ZIP Code)								
P.O. Box 3105 Anaheim, CA 92803	800 North Quincy Arlington, VA 22217								
4. NAME OF FUNDING SPONSORING ORGANIZATION	85. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER Contract NO0014-77-C-0636							
8c. ADDRESS (City, State and ZIP Code)	<u> </u>	10 SOURCE OF FUNDING NOS.							
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT				
11. TITLE Include Security Classification, Water Absorption and				NR 359-667					
conductivity in Poly(ethylene o	xide)-LiBF4 Film	s							
12 PERSONAL AUTHOR(S) M. M. Nicholson and T. P. Wei	smuller				-				
Technical 13b. TIME COVERED FROM 1-1-83 TO 12-31-8		14. DATE OF REPORT (Yr. Mo., Day) 3 October 1984 32		UNT					
16. SUPPLEMENTARY NOTATION	<u> </u>								
Prepared for publication in t	Prepared for publication in the Journal of the Electrochemical Society								
17. COSATI CODES	ontinue on reverse if ne	cessary and identi	ly by block numbers						
FIELD GROUP SUB. GR.		oxide), lithium tetrafluoroborate, tivity, syneresis							
19. ABSTRACT (Continue on reverse if necessary and									
Water-vapor absorption and conductivity in spin-cast poly(ethylene oxide) - lithium tetrafluoroborate films were investigated near 21°C by in situ near-infrared spectroscopy and ac conductance measurements. The film conductivity was 2 x 10 ohms cm until the water content exceeded that corresponding to LiBF4 3H20. It increased with additional water, reaching 3 x 10 ohms cm at the composition equivalent to LiBF4 20H20. Most of the water above the trihydrate level was unstably absorbed, however, and began to escape from the film within a few minutes. This syneresis was attributed to spontaneous restructuring or crystallization of the polymer. The conductivity data were interpreted on the basis of a two-phase model in which one portion of the salt remained in a nonconductive solid region, while the other portion dissolved in a more fluid conductive polymer-water region.									
20. DISTRIBUTION/AVAILABILITY OF ABSTRAC	21. ABSTRACT SECURITY CLASSIFICATION								
UNCLASSIFIED/UNLIMITED 🖫 SAME AS RPT.	Unclassified								
Jerry J. Smith	22b TELEPHONE NO Include Area Co (202) 696_44	de)	22c. OFFICE SYMBO						
	(202) 696-4409		UITA - COUE 4/2						



WATER ABSORPTION AND CONDUCTIVITY IN POLY(ETHYLENE OXIDE)-LITHIUM TETRAFLUOROBORATE FILMS

M. M. Nicholson*

Rockwell International Science Center

Anaheim, California 92803

T. P. Weismuller

Defense Electronics Operations

Rockwell International Corporation

Anaheim, California 92803

ABSTRACT

Water-vapor absorption and conductivity in spin-cast poly(ethylene oxide)-lithium tetrafluoroborate films were investigated near 21°C by in situ near-infrared spectroscopy and ac conductance measurements. The film conductivity was $\leq 2 \times 10^{-5}$ ohms⁻¹ cm⁻¹ until the water content

^{*}Active Electrochemical Society Member
Key words: Poly(ethylene oxide), lithium tetrafluoroborate, water, conductivity, syneresis.



exceeded that corresponding to LiBF $_4$ -3H $_2$ 0. It increased with additional water, reaching 3 x 10 $^{-3}$ ohms $^{-1}$ cm $^{-1}$ at the composition equivalent to LiBF $_4$ -2OH $_2$ 0. Most of the water above the trihydrate level was unstably absorbed, however, and began to escape from the film within a few minutes. This syneresis was attributed to spontaneous restructuring or crystallization of the polymer. The conductivity data were interpreted on the basis of a two-phase model in which one portion of the salt remained in a nonconductive solid region, while the other portion dissolved in a more fluid conductive polymer-water region.

	Accession For						
	NTIS GRA&I						
	DTIC TAB-						
	Unannounced 🔲						
(, 2)	Justific tism						
()	By						
	Distribution/						
	Availability Codes						
	Avail and/or						
	Dist Special						
	Λ.Ι						
	V1 - 1						
	C.L.						



Complexes of salts with aliphatic poly-ethers are a relatively new class of solid electrolytes (1,2). Some of these materials can attain conductivities of the order of 10⁻⁵ ohm⁻¹ cm⁻¹ at room temperature, and the conduction is known to increase greatly on absorption of water. Because of their potential importance for lithium battery electrolytes, most research on such complexes has been done with carefully dried preparations. For other types of batteries and electrochemical devices, however, some water is acceptable, or even required, and the higher conductivity is advantageous. The influence of water on these solids is, in any case, a point of scientific interest which has received only cursory treatment in previous studies.

This paper describes results of conductance measurements near 21°C on thin solid films of poly(ethylene oxide) (PEO) complexed with lithium tetrafluoroborate, and containing various amounts of water. The water content of the films was monitored in situ by near-infrared absorption spectroscopy while the ac conductance at 1,000 Hz was determined on an impedance bridge. This thin-film technique permitted much faster acquisition of data than conventional bulk methods for investigation of polymers. Both the water content and the conductance showed a peculiar but repeatable time dependence which probably was caused by spontaneous restructuring of the polymer.

THE REPORT OF THE PROPERTY OF



EXPERIMENTAL

The PEO preparation, with an average molecular weight of 4,000,000, was from Polysciences, Inc. The LiBF₄ was from Ozark-Mahoning. Electrolyte films of the order of 1 µm thick were prepared on single-crystal sapphire plates by spin casting from a viscous aqueous solution containing 4.5 polymer repeating units per molecule of LiBF₄. These plates had, near one edge, a pair of narrow-line electrodes formed from conductive silver paste, with an interelectrode spacing of 0.4 mm. Margins around the film were defined by masking tape, which was removed after the casting process.

The films were dried under vacuum at room temperature for 24 hr and transferred, without air exposure, to a helium-atmosphere glove box, where they were mounted in the double cell shown in Fig. 1. For the measurements of conductance and water absorption, the cell was placed in a Beckman DK-2A spectrophotometer, with the electrical leads connected to a Fluke Model 710B impedance bridge. Nitrogen containing known partial pressures of water was passed into the optical reference compartment of the cell and out through the sample compartment. The water pressure was controlled at known levels by passing the nitrogen through water in a cooled, thermostatted gas-washing bottle. The moist nitrogen then travelled through a long copper tube to reach room temperature, near 21°C, before entering the cell.



Resistances and near-infrared (IR) spectra of the films were determined at various times up to 2 hr, and, in some instances, the transmittance at the characteristic wavelength of the OH stretching band near 2.9 µm was recorded continuously as a function of time. The amount of water present per unit film area during an experiment was found by comparing the IR absorbance of the film with that of a known thickness of liquid water retained between two glass slides. Following a systematic run, the cell could be placed, open, in the vacuum chamber to re-dry the film in preparation for the next set of measurements.

Two methods were used to determine the original thickness of the PEO-LiBF $_4$ film after completion of the conductance measurements. The polymer electrolyte was too soft for measurement with a profilometer. For a rough thickness estimate ($\pm40\%$) the used film was re-dried, then dissolved in water, and the resulting weight loss noted. For a more accurate evaluation, the lithium content of the dissolved film was determined by atomic absorption. The density of the anhydrous PEO-LiBF $_4$ preparation was found to be 1.23 g/cm 3 by weighing a known volume of the bulk solid packed into a glass tube.



RESULTS AND DISCUSSION

The System PEO-LiBF₄-H₂O.--The PEO-LiBF₄ system at the 4.5:1 mole ratio was selected for investigation primarily because the anhydrous complex of this composition was known to have the comparatively high conductivity of 10^{-5} ohm⁻¹ cm⁻¹ at 20° C (1). This suggests a tendency toward amorphous behavior which could be conducive to the incorporation of water in the organic phase.

The PEO-LiBF $_4$ -H $_2$ O films were colorless and highly transparent. As expected, water was readily absorbed from the vapor phase with an immediate increase in conductivity. Figure 2 shows a typical set of near-infrared spectra recorded after thirty-minute exposures to each of the indicated partial pressures of water. The maximum absorption due to OH stretching occurred at 2.90 μ m in pure liquid water. This band acquired a doublet character in the PEO-LiBF $_4$ -H $_2$ O films, with increased absorption near 2.85 μ m, which was more evident at the lower water levels. The shift to the shorter wavelength apparently was due to binding of water with the lithium ion, since it did not occur with PEO in the absence of the salt.

Conductances (1/R) of two PEO-LiBF $_4$ films are plotted as functions of the water absorbance in Fig. 3 and 4. The symbol R represents the measured resistance of the film specimen. The anhydrous film thickness was roughly 1.8 μ m for Film 1 and, more accurately, 0.88 μ m for Film 2. The circles and other symbols represent different runs which covered a wide range of water pressures



and standing times, as well as different pre-drying conditions. noteworthy that the data for each film can be adequately represented by a single line, even though many nonequilibrium points are included. The significance of the slopes of these lines is discussed later. The absorbance intercept for Film 2 in Fig. 4 corresponds to the composition $LiBF_{4} \cdot 2.9H_{2}O$. The approximate composition $LiBF_{4} \cdot 2.5H_{2}O$ was found in a similar way for Film 1 in Fig. 3. Two hydrates of LiBF4 have been characterized in the literature (3,4). LiBF₄·H₂O is stable above 23°C in the presence of an aqueous solution of the salt, while $LiBF_4 \cdot 3H_2O$ crystallizes below 23°C. In the present study, near 21°C, the measured film conductances dropped abruptly to $<10^{-7}$ ohm⁻¹ as the water content fell below the trihydrate composition. It is thus apparent that the initial portion of the absorbed water was utilized primarily in hydration of the salt. The "free" water above the trihydrate level was responsible for the higher magnitude of conductivity discussed in this paper.

The absorption of water by the PEO-LiBF₄ films displayed an unusual time dependence. Figure 5 illustrates this behavior in the IR absorbance recorded under a constant water vapor pressure of 18.7 torr. After 24 hr of pre-drying under vacuum, the film added water rapidly at first. The absorbance then reached a maximum in 7 to 10 min, after which it gradually decayed toward the level corresponding to LiBF₄·3H₂0. This behavior was repeatable with thorough drying between runs. Less extensive drying produced a related, but distinctly different, result shown by the lower curve in Fig. 5. With a vacuum drying time of



0.5 hr, the initial absorbance again was essentially zero. The water uptake also was quite rapid at first, but the loss set in after only 1 min, and the IR absorbance approached the asymptotic value much earlier than it did with 24 hr of drying.

The change of conductance with time closely parallelled that of the water content, as one can infer from Fig. 3 and 4. This is shown explicitly by Fig. 6 for the same runs that are represented in Fig. 5.

The System PEO-H₂O.--It was of major interest to know whether the spontaneous water loss was a property of the salt or the polymer. A spin-cast film of PEO without the salt was prepared for this purpose and dried under vacuum 24 hr. Its infrared absorption under 18.7 torr of water vapor was then examined.

Infrared spectra recorded at various exposure times under constant water pressures are shown in Fig. 7. This group of spectra differs in several ways from the PEO-LiBF $_4$ -H $_2$ O spectra of Fig. 2. The salt-free film was visually cloudy, and infrared light scattering is evident in the lower transmission range of the spectra. Although the absorption maximum shifted slightly with water content, any doublet character of the OH band is not obvious. Finally, the salt-free spectra showed isosbestic points at 2.76 and 3.21 μ m. Such points are characteristic of a fixed stoichiometry between initial and final species in a chemical process. They were not observed with the nonscattering films

はいのできる。 でんかんのかん かっかんかい 一をこれなるのをしたる



containing LiBF₄. Fig. 8 indicates a time-dependent gain and subsequent loss of water by the PEO which is very similar to that for PEO-LiBF₄ in Fig. 5. The final water absorbance was relatively closer to zero, however, in the salt-free film.

Although the scattering effect prevented an absolute determination of water in the PEO, it is clear that the major time dependence was associated with the polymer. A comparable syneresis, or loss of solvent component, was reported by Weiss and Lenz for water in phosphonate esters derived from PEO aligomers (5). Those authors determined the absorbed water gravimetrically on bulk samples in experiments lasting several days. With the thin-film technique used here, the time dependence could be detected in a few minutes and well characterized in about an hour. An apparently related heat-induced syneresis in cross-linked PEO-H₂O gels was attributed by Graham et al. to increased ordering of the polymer, with some water still attached (6).

Further Correlations.--Conductivity relationships in the PEO-LiBF₄-H₂O system can be examined in greater detail by means of Fig. 9, in which the total thickness of the swollen film is considered, and Fig. 10, which treats the free water, with its incremental thickness, as a separate region supporting of all the observed conduction.



For calculating the bulk conductivity σ plotted in Fig. 9, the total film thickness was taken, as a first approximation, to be the sum of the dry PEO-LiBF4 thickness, based on bulk density, and the liquid water thickness equivalent to the IR absorbance of the film. This estimated total thickness ranged from 0.88 μ m in the dry state to 2.26 μ m for the swollen film at a ratio of 21 moles of H20 per mole of LiBF4. All of the smoothed data points for Film 2 fell close to a straight line intersecting the mole-ratio axis at 3.1. The corresponding plot for Film 1 was a slightly curved line with a similar intercept; it is not shown because of uncertainty in the dry-film thickness.

The cause of the linear relationship in Fig. 9. is not obvious. In a very simple model for the system, it could be envisioned that all of the salt dissolves in a homogeneous conductive phase, with water wacting only as a diluent. The conductivity would then decrease with increasing water content. Factors opposing this effect could be the dissociation of ion pairs and the lowering of viscosity on addition of water. However, those trends, superimposed on the dilution, would not account for the straight line in Fig. 9. The actual behavior was more consistent with a system of two microphases, one a conductive fluid or amorphous region containing dissolved salt, and the other a nonconductive solid including the remainder of the LiBF4·3H20. The linear relationship could then occur if the dissolved-salt concentration in the film as a whole were proportional to the free-water concent and the mobilities of Li⁺ and BF4 remained constant. This model treats the



conductive microphase as an aqueous region saturated with both PEO and LiBF₄ and disregards effects of porosity or tortuosity created by the solid PEO-salt matrix.

A lower limit for the apparent equivalent conductance of LiBF₄ can be estimated as follows from the plot in Fig. 9. At the mole ratio of 20, the concentration c of LiBF₄ dissolved in the entire film had to be ≤ 1.65 M. With the corresponding experimental conductivity σ of 3.1 x 10^{-3} ohms⁻¹ cm⁻¹, the equivalent conductance Λ_{L1BF_4} , expressed as $1000~\sigma/c$, would have been ≥ 1.9 ohms⁻¹ cm² mole⁻¹. It may be noted from the work of Radchenko and Ryss that LiBF₄ completely dissolves in pure water at a ratio as low as 5.35 moles of water per mole of salt (7). In the presence of PEO, however, the salt probably is much less soluble. The lower limit of 1.9 ohms⁻¹ cm² mole⁻¹ for Λ_{L1BF_4} is two orders of magnitude less than typical equivalent conductances of salts in water, but it is not inconsistent with their behavior in viscous polymer-water mixtures. For example, a paper by Isono et al. indicates an equivalent conductance of 7.9 ohms⁻¹ cm² mole⁻¹ for NaC1 in a concentrated poly(ethylene glycol)-water mixture at 25°C (8).

Figure 10 accentuates the contrast between the two types of film behavior encountered in this study. An incremental conductivity $\sigma_{\rm aq}$ was calculated by taking the effective film thickness as that equivalent to the free water. This incremental thickness was found from the IR absorbance



term A - A', where A is the measured absorbance and A' is the intercept from Fig. 3 or Fig. 4. These are nonequilibrium data. The pronounced difference between the plots in Fig. 10 may reflect a difference in the rates of syneresis for the two films: The polymer apparently rearranged readily in Film 1 to an ordered, or crystalline, phase, forming an aqueous region with a constant conductivity $\sigma_{\rm aq}$ of 6.2 x 10^{-3} ohms⁻¹ cm⁻¹. This water was subsequently lost by evaporation. With slower crystallization in Film 2, the data included some intermediate stages, where $\sigma_{\rm aq}$ was lower due to more polymer in solution. The same limiting level was eventually reached by Film 2, however, and water loss occurred as represented in Fig. 5.

Further research is planned to characterize related polymersalt-solvent electrolyte systems.

ACKNOWLEDGMENT

This work was performed in part by the Office of Naval Research.



REFERENCES

- M. B. Armand, J. M. Chabagno, and M. J. Duclot, p. 131 in
 P. Vashishta, J. N. Mundy, and G. K. Shenoy, Eds., "Fast Ion
 Transport in Solids," Elsevier North Holland, 1979.
- 2. D. F. Shriver, B. L. Papke, M. A. Ratner, R. Dupon, T. Wong, and M. Brodwin, Solid State Ionics, <u>5</u>, 83 (1981).
- 3. C. D. West, Z. Kristalloz, 91, 480 (1935).
- 4. K. C. Moss, D. R. Russell, and D. W. A. Sharp, Acta Cryst., 14, 330 (1961).
- 5. R. A. Weiss and R. W. Lenz, J. Appl. Polymer Sci., 23, 2443 (1979).
- 6. N. B. Graham, N. E. Nwachuku, and D. J. Walsh, Polymer, 23, 1345 (1982).
- 7. I. V. Radchenko and A. I. Ryss, J. Struct. Chem. U.S.S.R., <u>6</u>, 171 (1965).
- 8. T. Isono, K. Takahashi, and R. Tamamushi, Bull. Chem. Soc. Japan, 54, 2183 (1981).




ILLUSTRATIONS


- 1. Experimental cell
- 2. Infrared spectra of PEO-LiBF $_4$ -H $_2$ O film recorded 30 min after changes of ambient water vapor pressure
- 3. Dependence of measured conductance on IR absorbance due to water in Film 1
- 4. Dependence of measured conductance on IR absorbance due to water in Film 2. Inset shows the extrapolation in detail.
- 5. Time dependence of water absorbance in PEO-LiBF₄-H₂0 film recorded continuously under water pressure of 18.7 torr after different pre-drying times. All curves start at zero absorbance.
- 6. Time dependence of conductance of PEO-LiBF₄-H₂O film under conditions of Fig. 5. All curves start at zero conductance on this scale.
- 7. Infrared spectra of PEO-H₂O film recorded at different times under water pressure of 18.7 torr




- 8. Time dependence of water absorbance in PEO-H₂O film recorded continuously under water pressure of 18.7 torr after pre-drying 24 hr
- 9. Conductivity of swollen PEO-LiBF $_4$ -H $_2$ O film as a function of the mole ratio of H $_2$ O to LiBF $_4$. Points are smoothed data from Fig. 4.
- 10. Conductivity based on incremental thickness equivalent to free water in PEO-LiBF₄-H₂O films as function of free-water absorbance. Points are smoothed data from Fig. 3 and 4.



1. Experimental cell




2. Infrared spectra of PEO-LiBF $_4$ - H_2 0 film recorded 30 min after changes of ambient water vapor pressure




Dependence of measured conductance on IR absorbance due to water

in Film 1




4. Dependence of measured conductance on IR absorbance due to water in Film 2. Inset shows the extrapolation in detail.




Secondarics of the second of the second second of the seco

different pre-drying times. All curves start at zero absorbance. recorded continuously under water pressure of 18.7 torr after 5. Time dependence of water absorbance in PEO-LiBF $_4$ - $\mathrm{H}_2\mathrm{O}$ film




conditions of Fig. 5. All curves start at zero conductance on Time dependence of conductance of PEO-LiBF₄-H₂O film under 9.

this scale.



7. Infrared spectra of PEO-H₂O film recorded at different times under water pressure of 18.7 torr




Colors See Colors Colors Colors Colors

A CONTRACTOR OF STANDARD STAND


continuously under water pressure of 18.7 torr after pre-drying 8. Time dependence of water absorbance in PEO- $\mathrm{H}_2\mathrm{O}$ film recorded

24 hr



the mole ratio of $\mathrm{H}_2\mathrm{O}$ to LiBF $_4$. Points are smoothed data from Conductivity of swollen PEO-LiBF $_4$ -H $_2$ O film as a function of

Fig. 4.



Conductivity based on incremental thickness equivalent to free absorbance. Points are smoothed data from Fig. 3 and 4. water in PEO-LiBF $_4$ -H $_2$ O films as function of free-water 2

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	No. Copies		No. Copies
Office of Naval Research Attn: Code 413 800 N. Quincy Street Arlington, Virginia 22217	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 5042 Crane, Indiana 47522	1	Naval Weapons Center Attn: Dr. A. B. Amster Chemistry Division China Lake, California 93555	1
Commander, Naval Air Systems Command Attn: Code 310C (H. Rosenwasser) Washington, D.C. 20360	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko Port Hueneme, California 93401	1	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 2770	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 1911	.2
DTNSRDC Attn: Dr. G. Bosmajian Applied Chemistry Division Annapolis, Maryland 21401	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375	1		

Dr. Paul Delahay Department of Chemistry New York University New York, New York 10003

Dr. P. J. Hendra
Department of Chemistry
University of Southampton
Southampton S09 5NH
United Kingdom

Dr. T. Katan Lockheed Missiles and Space Co., Inc. P.O. Box 504 Sunnyvale, California 94088

Dr. D. N. Bennion
Department of Chemical Engineering
Brigham Young University
Provo, Utah 84602

Mr. Joseph McCartney Code 7121 Naval Ocean Systems Center San Diego, California 92152

Dr. J. J. Auborn
Bell Laboratories
Murray Hill, New Jersey 07974

Dr. Joseph Singer, Code 302-1 NASA-Lewis 21000 Brookpark Road Cleveland, Ohio 44135

Dr. P. P. Schmidt Department of Chemistry Oakland University Rochester, Michigan 48063

Dr. H. Richtol Chemistry Department Rensselaer Polytechnic Institute Troy, New York 12181

Dr. R. A. Marcus Department of Chemistry California Institute of Technology Pasadena, California 91125

Dr. E. Yeager Department of Chemistry Case Western Reserve University Cleveland, Ohio 44106

Dr. C. E. Mueller
The Electrochemistry Branch
Naval Surface Weapons Center
White Oak Laboratory
Silver Spring, Maryland 20910

Dr. Sam Perone
Chemistry & Materials
Science Department
Lawrence Livermore National Laboratory
Livermore, California 94550

Dr. Royce W. Murray
Department of Chemistry
University of North Carolina
Chapel Hill, North Carolina 27514

Dr. B. Brummer EIC Incorporated 111 Downey Street Norwood, Massachusetts 02062

Dr. Adam Heller Bell Laboratories Murray Hill, New Jersey 07974

Electrochimica Corporation Attn: Technical Library 2485 Charleston Road Mountain View, California 94040

Library
Duracell, Inc.
Burlington, Massachusetts 01803

Dr. A. B. Ellis Chemistry Department University of Wisconsin Madison, Wisconsin 53706

Dr. Manfred Breiter
Institut fur Technische Elektrochemie
Technischen Universitat Wien
9 Getreidemarkt, 1160Wien
AUSTRIA

Dr. M. Wrighton
Chemistry Department
Massachusetts Institute
of Technology
Cambridge, Massachusetts 02139

Dr. B. Stanley Pons Department of Chemistry University of Utah Salt Lake City, Utah 84112

Donald E. Mains
Naval Weapons Support Center
Electrochemical Power Sources Division
Crane. Indiana 47522

S. Ruby
DOE (STOR)
M.S. 68025 Forrestal Bldg.
Washington, D.C. 20595

Dr. A. J. Bard
Department of Chemistry
University of Texas
Austin, Texas 78712

Dr. Janet Osteryoung Department of Chemistry State University of New York Buffalo, New York 14214

Dr. Donald W. Ernst Naval Surface Weapons Center Code R-33 White Oak Laboratory Silver Spring, Maryland 20910

Mr. James R. Moden Naval Underwater Systems Center Code 3632 Newport, Rhode Island 02840

Dr. Bernard Spielvogel U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709

Dr. Aaron Fletcher Naval Weapons Center Code 3852 China Lake, California 93555 Dr. M. M. Nicholson Electronics Research Genter Rockwell International 3370 Miraloma Avenue Anaheim, California

Dr. Michael J. Weaver
Department of Chemistry
Purdue University
West Lafayette, Indiana 47907

Dr. R. David Rauh EIC Laboratories, Inc. 111 Downey Street Norwood, Massachusetts 02062

Dr. Aaron Wold
Department of Chemistry
Brown University
Providence, Rhode Island 02192

Dr. Martin Fleischmann Department of Chemistry University of Southampton Southampton SO9 5NH ENGLAND

Dr. R. A. Osteryoung
Department of Chemistry
State University of New York
Buffalo, New York 14214

Dr. Denton Elliott
Air Force Office of Scientific
Research
Bolling AFB
Washington, D.C. 20332

Dr. R. Nowak Naval Research Laboratory Code 6170 Washington, D.C. 20375

Dr. D. F. Shriver
Department of Chemistry
Northwestern University
Evanston, Illinois 60201

Dr. Boris Cahan Department of Chemistry Case Western Reserve University Cleveland, Ohio 44106

Dr. David Aikens Chemistry Department Rensselaer Polytechnic Institute Troy, New York 12181

Dr. A. B. P. Lever Chemistry Department York University Downsview, Ontario M3J1P3

Dr. Stanislaw Szpak Naval Ocean Systems Center Code 6343, Bayside San Diego, California 95152

Dr. Gregory Farrington
Department of Materials Science
and Engineering
University of Pennsylvania
Philadelphia, Pennsylvania 19104

M. L. Robertson
Manager, Electrochemical
and Power Sources Division
Naval Weapons Support Center
Crane, Indiana 47522

Dr. T. Marks
Department of Chemistry
Northwestern University
Evanston, Illinois 60201

Dr. Micha Tomkiewicz Department of Physics Brooklyn College Brooklyn, New York 11210

Dr. Lesser Blum
Department of Physics
University of Puerto Rico
Rio Piedras, Puerto Rico 00931

Dr. Joseph Gordon, II IBM Corporation K33/281 5600 Cottle Road San Jose, California 95193

Dr. Hector D. Abruna Department of Chemistry Cornell University Ithaca, New York 14853 Dr. D. H. Whitmore Department of Materials Science Northwestern University Evanston, Illinois 60201

Dr. Alan Bewick Department of Chemistry The University of Southampton Southampton, SO9 5NH ENGLAND

Dr. E. Anderson NAVSEA-56Z33 NC #4 2541 Jefferson Davis Highway Arlington, Virginia 20362

Dr. Bruce Dunn
Department of Engineering &
Applied Science
University of California
Los Angeles, California 90024

Dr. Elton Cairns
Energy & Environment Division
Lawrence Berkeley Laboratory
University of California
Berkeley, California 94720

Dr. D. Cipris
Allied Corporation
P.O. Box 3000R
Morristown, New Jersey 07960

Dr. M. Philpott
IBM Corporation
5600 Cottle Road
San Jose. California 95193

Dr. Donald Sandstrom Boeing Aerospace Co. P.O. Box 3999 Seattle, Washington 98124

Dr. Carl Kannewurf
Department of Electrical Engineering
and Computer Science
Northwestern University
Evanston, Illinois 60201

Dr. Richard Pollard
Department of Chemical Engineering
University of Houston
4800 Calhoun Blvd.
Houston, Texas 77004

Dr. Robert Somoano Jet Propulsion Laboratory California Institute of Technology Pasadena, California 91103

Dr. Johann A. Joebstl USA Mobility Equipment R&D Command DRDME-EC Fort Belvoir, Virginia 22060

Dr. Judith H. Ambrus NASA Headquarters M.S. RTS-6 Washington, D.C. 20546

Dr. Albert R. Landgrebe U.S. Department of Energy M.S. 6B025 Forrestal Building Washington, D.C. 20595

Dr. J. J. Brophy Department of Physics University of Utah Salt Lake City, Utah 84112

Dr. Charles Martin Department of Chemistry Texas A&M University College Station, Texas 77843

Dr. H. Tachikawa Department of Chemistry Jackson State University Jackson, Mississippi 39217

Dr. Theodore Beck Electrochemical Technology Corp. 3935 Leary Way N.W. Seattle, Washington 98107

Dr. Farrell Lytle Boeing Engineering and Construction Engineers P.O. Box 3707 Seattle, Washington 98124

Dr. Robert Gotscholl Ms. Wendy Parkhurst
U.S. Department of Energy Naval Surface Weapons Center R-33
MS G-226 Silver Spring, Maryland 20910
Washington, D.C. 20545

Dr. Edward Fletcher Department of Mechanical Engineering University of Minnesota Minneapolis, Minnesota 55455

Dr. John Fontanella Department of Physics U.S. Naval Academy Annapolis, Maryland 21402

Dr. Martha Greenblatt Department of Chemistry Rutgers University New Brunswick, New Jersey 08903

Dr. John Wasson Syntheco, Inc. Rte 6 - Industrial Pike Road Gastonia. North Carolina 28052

Dr. Walter Roth Department of Physics State University of New York Albany, New York 12222

Dr. Anthony Sammells Eltron Research Inc. 4260 Westbrook Drive, Suite 111 Aurora, Illinois 60505

Dr. W. M. Risen Department of Chemistry **Brown University** Providence, Rhode Island 02192

Dr. C. A. Angell Department of Chemistry Purdue University West Lafayette, Indiana 47907

Dr. Thomas Davis Polymer Science and Standards Division National Bureau of Standards Washington, D.C. 20234

